



DISTRIBUTED BY

**Installation Tools** 



advancecomponents.com

972-446-5500



Charger charging time to - 22 / 30 minutes 90% / 100%

## **GB110A SERIES**

• GB110A Includes (1) VP1086 (2Ah Battery) • GB 110A/2 Includes (2) VP1086 (2Ah Batteries)

• GB110A-4AH Includes (1) VP1357 (4Ah Battery) • GB110A/2-4AH Includes (2) VP1357 (4Ah Batteries)

HONSEL

BOM®, MAGNA-GRIP®, C6L®, LGP® & NAS® ARE REGISTERED TRADEMARKS OF ARCONIC INC.

## **GB110A SERIES**

- GB110A Includes (1) VP1086 (2Ah Battery)
- GB 110A/2 Includes (2) VP1086 (2Ah Batteries)
- GB110A-4AH Includes (1) VP1357 (4Ah Battery)
- GB110A/2-4AH Includes (2) VP1357 (4Ah Batteries)

## **INSTALLS: 5/32"-1/4" LOCKBOLTS**



AND 1/4" BOM® (Repair Only)



# DISTRIBUTED BY



advancecomponents.com

972-446-5500



GB110A - SELECTION CHART				
FASTENER	DIA.	STRA	NGHT	OFFSET
C6L® LOCKBOLTS	3/16	LB06-722-20	LB06-722-60	
	1/4 3/16	LB08-722-20 MG06-722-20	LB08-722-60 MG06-722-60	
MAGNA-GRIP® LOCKBOLTS	1/4	MG08-722-20 MG08-722-20	MG08-722-60	
LGP® LOCKBOLT	5/32	LGP05-2480-10	LGP05-2480-20	
LGPL2SC-V BACB30VM LGPL18SC-V BACB30XT		LGP05-2480-45		
LGPL4SC-V ABS0548	3/16	LGP06-2480-10	LGP06-2480-20	
LGPL2SP-V BACB30VN LGPL4SP-V ASNA2392		LGP06-2480-45		
LGPL8SC-V BACB30WD LGPL9SC-V BACB30WB	1/4	LGP08-2480-10	LGP08-2480-20	
LGPL9SP-V BACB30VY	1/4	LGP08-2480-45	20100-2400-20	
BACB31N BACB31P				
M GP® (MLLMETER) LOCKBOLT	4 MM	MGP4-730B-10 MGP4-2480-45	MGP4-2480-20	
	5 MM	MGP5-730B-10	MGP5-2480-20	
		MGP5-2480-45		
	6 MM	MGP6-730B-10	MGP6-2480-20	
	4 MM	MGP6-2480-45 MLGP4-730B-10	MLGP4-2480-20	
MLGP® (MLLMETER) LOCKBOLT		MLGP4-2480-45		
	5 MM	MLGP5-730B-10	MLGP5-2480-20	
	6 MM	MLGP5-2480-45 MLGP6-730B-10	MLGP6-2480-20	
		MLGP6-2480-45		
NAS and GP® SHEAR/TENSION LOCKBOLTS	5/32	NA SS05-2480-10 NA SS05-2480-20	NAST05-2480-10 NAST05-2480-20	
BACB30TY BACB30UA BACB30TZ BACB30UB		NASS05-2480-45	NAST05-2480-45	
BACB30DY BACB30GX BACB30DX BACB30GP	3/16	NAS06-730B-10	NA S06-2480-20	
BACB30GO BACB30GY	1/4	NAS06-2480-45 NAS08-730B-10	NA S08-2480-20	
BACB30GW		NAS08-2480-45		
CONTAINER BOLT (R 12) HLPP, HLPM, HLPE, HLPS	3/8	HT12-713-20		
HLPSC & HLPSM				
BLIND BOLT (SINGLEACTION)	5/32	SB05-752C-20	SB05-752C-45	SB05-752B-43OS
WITH OR W/OUT DRIVE WASHER MS90353S & U / MS90354S & U		SB05-752C-80		
MS21140S & U / MS21141S & U	3/16	SB06-752B-20	SB06-752B-45	SB06-752B-43OS
MAXI-BOLT®, BACB30YY, YU, & YT		SB06-752B-80		
BLIND BOLT (SINGLEACTION) WITH DRIVE WASHER	5/32	UBB05-752C-20 UBB05-752C-80	UBB05-752C-45	UBB05-752B-43OS
MS90353S & U / MS90354S & U				
MS21140S & U / MS21141S & U CR7000 SERIES, BACB30YY, YU, & YT	3/16	UBB06-752B-20	UBB06-752B-45	UBB06-752B-43OS
EN6122 & UAB130-EU		UBB06-752B-80		
EN6127 & UAB6127-EU	5/32 3/16	UAB568-713-21	UAB568-713-61	UAB05-752B-43OS
EN6128 & UAB100-EU EN6129 & UABP-EU	1/4	(INSTALLS 5/32", 3/16" & 1/4")	(INSTALLS 5/32", 3/16" & 1/4")	UAB06-752B-43OS
	1/8	SMLS04-108-23		SMLS04-752B-430S
BLIND RIVET (SINGLE ACTION) WITH OR W/OUT DRIVE WASHER	5/32	SMLS05-108-23		SMLS05-752B-43OS
NAS1900 S & U SERIES	3/16	SMLS06-108-23		SMLS06-752B-43OS
"A" CODE NAS1398A & NAS1399A	1/4 3/32	SMLS08-713-20 3A-108-23		SMLS08-752B-43OS (aluminum only) 3A-752B-43OS
	1/8	4A-108-23		4A-752B-430S
	5/32	5A-108-23		5A-752B-43OS
	3/16 1/4	6A-108-23 SMLS08-713-20		6A-752B-43OS
T RIVET®	3/16	6T-352-21	6T-352-61	
PROTRUDING HEAD,	1/4 3/16	8T-352-21	8T-352-61	
MULTI-GRIP BLIND RIVETS	3/16	MGL06-752A-21 MGL08-752A-21	MGL06-752A-61 MGL08-752A-61	
MONOBOLT®	3/16	MB06-752A-21	MB06-752A-61	
	1/4	MB08-752A-21	MB08-752A-61	
TLR RIVET®	1/4 1/8	8TLR-352-21	8TLR-352-61	AEGNAN 704 4000
CHERRY MAX®, CHERRY MAX® 'AB',	5/32	456MAX-108-23 (INSTALLS 1/8", 5/32" & 3/16")		456MAX-731-43OS (INSTALLS 1/8", 5/32" & 3/16")
BACR15FR/FP, BACR15GF/GK	3/16 1/4	08MAX-752B-20	08MAX-752B-45	
A SP®	1/4	ASP06-752C-20	ASP06-752C-45	ASP06-752B-43OS
ASP 2, ASP PF, ASP 4 FF, ASP 2 F, ASP 2 LC	17/64	ASP08-752B-20	ASP08-752B-45	ASP08-752B-43OS
STANDARD MBO®	21/64 1/8	ASP10-713-20 MBC04-108-23	ASP10-713-45	MBC04-752C-43OS
NAS1719, NAS1720	5/32	MBC05-108-23		MBC04-752C-43OS MBC05-752C-43OS
NAS1721	3/16	MBC06-108-23		MBC06-752C-43OS
MBO® LOCK CREATOR NAS1719X(L), NAS1720X(L)	1/8 5/32	456MAX-108-23		456MAX-731-43OS
NAS1713X(L), NAS1720X(L)	3/16	(INSTALLS 1/8", 5/32" & 3/16")		(INSTALLS 1/8", 5/32" & 3/16")
GROUND STUD,	8/32	GS8-752C-20	GS8-752C-45	GS8-752B-43OS
M83454 BACS53B	10/32 3/32	GS10-752B-20 3N-108-23	GS10-752B-45	GS10-752B-43OS 3N-751A-43OS
Por® open end Nail Rivet	1/8	4N-108-23		4N-751A-430S
	5/32	5N-108-23		5N-751A-43OS
	3/16 1/4	6N-108-23 8CN-713-21	8CN-713-61	6N-751A-430S
	3/32	3N-108-23	UCINE / 13-01	3N-751A-430S
POP® CLOSED END NAIL RIV ET	1/8	4CEA-108-23		4CEA-751-43OS
(ALUMINUM MANDREL)	5/32 3/16	5CEA-108-23		5CEA-751-43OS
	3/16 3/32	6CEA-108-23 3N-108-23		6CEA-751-43OS 3N-751A-43OS
POP® CLOSED END NAIL RIV ET	1/8	4CES-108-23		4CES-751-43OS
(STEEL MANDREL)	5/32 3/16	5CES-108-23 6CES-108-23	5CES-352-61	5CES-751-43OS
CHERRYMAX®, MAXI-BOLT®, AND MBC ® ARE RE			6CES-352-61 ACE.MONOBOLT®IS A REGISTERE	6CES-751-43OS D TRADEMARK OF AVDEL UK LIMITED.
A SP ®, GP ®, LGP ®, N	IGP 68, MLGP	8, MAGNA-GRIP & AND C6L&ARE R	EGISTERED TRADEMARKS OF ARC	ONIC INC.
GAGE BILT CERTIFIES THE GB110A WILL INSTALL THE ABOVE FASTENERS				

NOTE: THE LAST 2 DIGITS OF THE NOSE ASSY REPRESENTS THE LENGTH THE NOSE EXTENDS FROM THE TOOL LE -23 = 2.3 INCHES

9/21



#### **GB101 SERIES**

• GB101 Includes (1) VP1400 (2Ah Battery) • GB101/2 Includes (2) VP1400 (2Ah Batteries)



Rated Pull Load - 2,248 lbs. (10 kN)

Charger charging time to - 22 / 30 minutes 90% / 100%

### **GB106 SERIES**

• GB106 Includes (1) VP1309 (2Ah Battery) • GB 106/2 Includes (2) VP1309 (2Ah Batteries)



# **GB107 SPECIFICATIONS**

Weight (Incl. battery) Sound Emissions Vibrations ah / K [m/s<sup>2</sup>] Total Stroke Rated Pull Load Charger charging time to - 3.5 lbs. (1.6 kg) - <65 / 3 // <76 / 3 (LpA / K // LWA / K [dB] - <2.5 / 1.5 - .984" (25 mm) - 2,248 lbs. (10 kN) - 22 / 30 minutes 90% / 100%





• GB108 Includes (1) VP1086 (2Ah Battery) • GB 108/2 Includes (2) VP1086 (2Ah Batteries)



### **GB 116RN SPECIFICATIONS**

Weight (Incl. battery) - 5.3 lbs. (2.4 kg)

Total Stroke - .787" (20 mm)

Rated Pull Load - 5,620 lbs. (25 kN)

Charger charging time to - 22 / 30 minutes 90% / 100%





• GB128 Includes (1) VP1086 (2Ah Battery) • GB 128/2 Includes (2) VP1086 (2Ah Batteries)